

1/8 - (C) FILE CAPLUS

STN CA Caesar accession number : 1849

AN - 2003:592347 CAPLUS

DN - 139:280339

TI - Identification of risk scenarios in the phenol-acetone process. Part II:  
the cumene hydroperoxide cleavage section

AU - Pellegrini, Laura; Bonomi, Susi; Biardi, Giuseppe

CS - Department of Chemistry, Materials and Chemical Engineering "G. Natta",  
Politecnico di Milano, Milan, Italy

SO - Proceedings of the Annual Loss Prevention Symposium (2002), 37th, 565-576  
CODEN: PALSF9

PB - American Institute of Chemical Engineers

DT - Journal

LA - English

AB - The CHP cleavage section is the second reaction unit in the flowsheet for phenol-acetone prodn.: the cleavage takes place in two tubular reactors, each of them incorporating two cooling sections. Kinetics is very fast and low contact times are required. A high recirculation ratio has to be applied to keep CHP concn. low enough. Like the cumene oxidn. unit the Dow Fire and Explosion Index has been calcd. for hazard identification, showing that the degree of hazard for the cleavage reactor falls within the class of moderate risks according to the Dow classification. Then the dynamic simulation of this section has been performed in order to identify risk scenarios. It is well known that the chance of CHP thermal decompn. increases as CHP concn. and/or operating temp. increase. An increase in CHP concn. may occur because of a reaction stop, mainly due to neutralization of H<sub>2</sub>SO<sub>4</sub>, the catalyst, by means of NaOH coming from the preceding sections of the plant.